





| FEATURES  | F5011<br>F6011   | F5021<br>F6021  | F5061<br>F6061  |
|---|--|---|---|
|  |  |  |  |
| Channels  | 8  | 128   | 512   |
| Power Output (VHF/UHF)  | 45/50W   | 45/50W  | 45/50W  |
| Display   | Interative LED   | Yes   | Yes   |
| MDC Signaling   | Limited  | Basic   | Full  |
| Tone Signaling  | Yes  | Yes   | Yes   |
| Encryption  | Optional Board   | Optional Board  | Built-in  |
| GPS   |  |   | Optional  |
| Connector Access  | Optional   | Optional  | DB25  |
| LTR®  |  |   | Yes   |
| Upgradable to Digital   |  |   | IDAS™   |
| Detachable Front Panel  |  |   | Yes   |
| <b>KENWOOD®</b>   | TK-7302/8302   | TK-7360.8360  | TK-7180/8180  |
| <b>VERTEX®</b>  | VX-2100, VX-4500   | VX-2200   | VX-4600   |

### Legend

|  |   |   |   |
|--|---|---|---|
| <b>Good</b>  | <b>Better</b>   | <b>Best</b>   | <b>No</b>   |
|  |  |  |  |

\*Typical operation Tx:Rx: Stand-by = 5:5:90, power save ON.